

Speedseed 1500

The Speedseed models are ideal to overseed large areas quickly. The individual conical ring sections create seed pockets in the soil in which seed is accurately delivered, the holes are then closed with the roller; the additional spike rear roller increases the holes to 1840 per m².



| Specifications | |
|-----------------------------------------------------------|-----------------------|
| SKU | 124.160.006 |
| Working width (m) | 1.5 |
| Working width (inch) | 59 |
| Max. Working depth (mm) | 5 - 20 |
| Max. Working speed (km h) | 12 |
| Working speed (mph) | 7.5 |
| Weight (kg) | 468 |
| Weight (lbs) | 1030 |
| Disc spacing (mm) | 30 |
| Disc spacing (inch) | 1.18 |
| Hopper capacity (ltr) | 224 |
| Hopper capacity (cu.ft.) | 7.84 |
| Number of holes single spiked roller (m ²) | 990 |
| Number of holes single spiked roller (sq.yd) | 783 |
| Min. Tractor HP required | 30 |
| Three-point hitch | 3-point CAT 1-2 |
| Lubricant | EP2 |
| Min. lifting capacity 610mm behind the lifting eyes (kg) | 550 |
| Min. lifting capacity 610mm behind the lifting eyes (lbs) | 1212 |
| Updated | 2022-11-23 14:52:18.0 |